

# INSTALLATION INSTRUCTIONS

## STEP 180 PLUS



HIDEAWAY SOLUTIONS  
www.hideawaysolutions.com  
(401) 420-2042

### MODEL SIZES:

Height: 34 1/4" (870 mm) Depth: ☐ 20 7/8" (530 mm) ☐ 23" (584 mm)  
☐ 23 5/8" (600 mm) ☐ 26 3/4" (680 mm)

OR

Height: 32" (813 mm) Depth: ☐ 20 7/8" (530 mm)  
☐ 23 5/8" (600 mm)

### WARNINGS:




- Never use step unit as a portable step stool.
- Only use step unit when properly installed into the cabinet mounting guide.
- Always use designated handle area to operate.
- Keep hands free of pinch zones when operating step unit.
- Always check surroundings when lowering step unit.
- Always assist children when operating and using step unit.

### NOTES:

- The following instructions contain information on how to install and use the STEP 180 PLUS step unit.
- The STEP 180 PLUS has been designed to be used between two base cabinets or between a base cabinet and a rigid end panel.
- See "Installation Options" for more details and diagrams.
- Save these instructions for future use and reference.
- Improper installation voids the warranty. If you have any problems with Step 180 PLUS unit please contact Hideaway Solutions directly.
- One year limited warranty - Details on Pg. 7

### Parts:



## Complete The Following Installation Instructions Using:

----- Pencil  
----- Drill  
----- #2 Phillips head bit  
----- Long Drill bit size 3/16"

Tape Measure -----  
Carpenter Square and/or Level -----  
Wood Glue -----  
Nail gun and/or Tape -----

### Guidelines:

- (1) - Step unit is designed to be attached between 2 base cabinets or a base cabinet and end panel.
- (2) - For smooth operation of the step unit, finished floor height must be the same height under the cabinets as the rest of the room.
- (3) - Installation instructions assume countertops to be installed after step unit installation.

# Attaching Mounting Guide: Base Cabinet To Base Cabinet/End Panel:


**Note:** Follow Step 1 For Face Frame Constructed Cabinets Only,  
For European Style Cabinets, Continue To Step 2

If your cabinets have a face frame overhang (where the face frame extends past the cabinet's exterior side panel), an additional spacer/shim will be needed. The spacer/shim aligns and supports installation of the mounting guide.  
(Two) 3/16" (4.8mm) thick plastic spacer/shims are provided.

**1.**

Use the provided spacer/shim OR cut spacer/shim to recommended size by measuring face frame overhang thickness A (see box below).

**Note:** Custom Cut Spacer/Shim May Be Needed Depending On Face Frame Overhang Dimension (A). It Should Be Sized To Support The Entire Side(s) Of The Mounting Guide.  
**Recommended Material:** Wood **Number of shims:** 2  
**Recommended Size:** 1 1/2" (38mm) x 5 1/2" (140mm) x Thickness A



**Note:** The Following Instructions Are Not Dependent On The Orientation Of The Cabinets Shown In The Diagrams.


**2.**

Install, level and securely attach 1st cabinet to which the mounting guide will be attached.

Determine what height Step 180 PLUS model you have:  
(This number determines the installation height of the mounting guide.)

**A** **B**  
Height = 32" (813 mm) or 34.25" (870 mm)

Mark a level line along the side of the cabinet at the Height = A or B above the finished floor.



**Note:** The Mounting Guide Has Multiple Mounting Holes For Different Mounting Options. (see Alternative mounting guide Installation PG. 3)

**Note:** Modification Or Removal Of The Cabinet Corner Bracket/ Countertop Support May Be Needed If They Are Obstructing The Mounting Guide's Hole Locations.



**3. Choose the cabinet type that best fits your installation:**

**Frameless/ Overlay Cabinets** - hold the top edge of the mounting guide on the marked line and align the front of the mounting guide with the front of the cabinet frame. (FIG. 1)

Or


**Full-inset Cabinets** - hold the top edge of the mounting guide on the marked line and align the front of the mounting guide 3/4" back (i.e. the thickness of face panel) from the front edge of cabinet frame (FIG. 2)

**4.** Using a 3/16" bit, insert the drill bit through the 3rd mounting hole on the side of the mounting guide. Align the drill bit to go through the adjacent hole on the other side of the mounting guide and continue to drill through the side of the cabinet.






**5.** In order to keep the mounting guide aligned for the next step, temporarily insert a 4" machine screw through both the inside of the base cabinet and through the 3rd side holes of the mounting guide. Screw wingnut onto machine screw and hand tighten.




**6.** Secure the front of the mounting guide to the cabinet: While keeping the top edge of the mounting guide level along the marked line, screw a 5/8" flat head screw (provided) through the 1st angled hole of the mounting guide and into the cabinet.



**7.** Unscrew wingnut and remove 4" (102mm) machine screw in order to install 2nd cabinet (or end panel).


**8.** Install, level, and secure 2nd cabinet/endpanel flush against adjacent side of mounting guide, making sure of a consistent 1 1/2" (38.1mm) parallel vertical space between the two cabinets face frames. Check for parallel horizontal spacing between the two cabinets face frames as well.

**9.** While securing the mounting guide re-insert the 3/16" drill bit into the same 3rd hole and drill through the 2nd cabinet.




**10.** Insert the 4" (102mm) machine screw again through the same 3rd hole, all the way through the 1st cabinet, mounting guide and 2nd cabinet. Add the lock washer onto the bolt and screw and tighten the provided wingnut onto the 4" (102mm) machine screw.

**Warning:** Do not over tighten the wingnut. Over tightening the wingnut may compress the mounting guide causing it to pinch and squeeze against the top rail when operating the step unit.




**11.** Screw a 5/8" flat head screw (provided) through the other 1st hole on the opposite side of the Mounting Guide and secure the mounting guide to the front of the 2nd cabinet.


Double check for a consistent 1 1/2" (38.1mm) vertical spacing between the two cabinets or cabinet and end panel.



## Alternative Mounting Guide Installation (Ex. Different Depth Cabinets)

If access to installing either or both screws in step 11 is difficult, two 4" (102 mm) machine screws can be used for installing the mounting guide to the cabinets. Follow steps 1 through 10 by using the 2nd and 4th side holes of the mounting guide instead of the 3rd side hole. Do not over tighten wingnuts.





1. Locate the area where the guide pads will be installed (Step 2 and 3) and wipe down the area so it's clean and dry.
2. The guide pads are mounted on the exterior, side surface of the cabinet.  
The bottom of the guide pads mount at 4 3/4" (120mm) above the finished floor. See (FIG. 1)
3. Position the guide pads so that the guide pads are **flush** with the front edge of the cabinet frame. See (FIG. 2)
4. Remove the paper back of the sticky end of the guide pads and attach to the side of each cabinet/endpanel. Press firmly.

## Installing/Removing Step 180:


**Caution:** The step unit uses a magnetic latch. When lifting or handling, extra care is needed to prevent unintentional release of the steps.

**Note:** In The Following Steps The Top Rail Of The Step Unit Will Slide Through The Channel Of The Mounting Guide (Diagram Showing Front View).

**Important:** Test the sliding action of the step unit: make sure there are no problems with the installation of the mounting guide before countertops are installed.


The step unit should slide easily in and out of the mounting guide. If the step unit has trouble sliding smoothly;

1. Check the mounting guide is not tilted or askew in anyway.
2. Check the mounting bolt(s) securing the mounting guide are not over tightened.
3. Check the parallel vertical spacing between the (2) adjacent cabinets, from top to bottom is, 1 1/2" (38.1mm).



1. Carefully position the step unit in front of the cabinet opening. Align the step unit to slide into the opening.
2. Pivot the step unit back onto its rear wheel, allowing the top rear corner of the step unit low enough for the Adjustable Stop to clear the lower portion of the mounting guide.


Continue On Next Page....



## Installing/Removing Step 180:

**3.** Carefully slide the complete step unit back until the top rail slides into the mounting guide and the Adjustable Stop travels past the bottom of the mounting guide block.  
(See diagram in Step 5)


**4.** Pivot the step unit back down and guide the step unit into the space between the cabinets.



**5.** Once both wheels are on the ground, with the Adjustable Stop positioned behind the mounting guide, the step unit can be moved back and forth within the space between the cabinets.

**Note:** Adjustable Stop **MUST** be behind the mounting guide block for correct installation and before use of the step unit.

**Removal:** Reverse Order Of (Steps 1-5).




## Installing The Face panel: (Not Included)

**Note:** Face panel strip should be cut-to-size and at least 1 1/4" (31.8mm) wide. The general height should extend from the top of the toe kick up to the countertop, matching the adjacent cabinet face panels.

**1.** Measure and drill location for attaching cabinet handle/knob (not included) Countersinking the backside handle/knob screw(s) is recommended to allow for the face panel to fit flush against the face panel mounting plate.

**2.** On the front of the face panel mounting plate, peel paper back off the top and bottom sticky mounting squares. The middle mounting square paper can remain unused, in case a second attempt is needed.

**3.** Align the face panel in the desired location and press face panel onto the face panel mounting plate, sticking the two together.




**4.** With the step unit in the deployed position (shown), secure the face panel to the mounting plate using the holes in the back side of the mounting plate with the following screws (included): (Pre-drill holes if necessary)

- One 5/8" (15.9mm) Flat Head Screw (Top Hole).
- One 5/8" (15.9mm) Flat Head Screw (Middle Hole).
- One 2" (51mm) Flat Head Screw (Bottom Hole).

**Note:** Angled Access To The Bottom 2" Screw Is Easier With A "Long" Phillips Head Bit Or Screwdriver.

**5.** An (optional) face panel bumper is provided. Attach the bumper on the top portion of the back side of the step unit's face panel. Align so that when in the closed position, the bumper contacts the front flat portion of the mounting guide.






## Adjustable Face Panel:

## Installing Toe Kick:

**Adjustments:** ½" fore and aft range of adjustment of the Handrail allows for the Step Unit Face Panel to align vertically with the adjacent cabinet face panels:


1. Loosen the Adjustment Screw located in the elongated hole on the top side of the Handrail.
2. Move Handrail fore or aft to align the Face Panel to adjacent cabinet face panels and retighten screw.



## Installing The Toe Kick With Cut-To-Size Toe Kick Extension: (Toe Kick Material Not Included)


### Guidelines:

- The following instructions are meant to be followed before toe kick material is installed on adjacent cabinetry.
- Use the same toe kick material as the adjacent cabinet toe kicks.
- Recommended minimum clearance of 1/16" (1.6mm) between either side of the step unit's toe kick and the adjacent cabinet toe kicks.
- Recommended minimum clearance of 3/16" (4.5mm) between the bottom of the toe kick and the floor.
- Beveling the backsides of the step unit's toe kick can help avoid any binding with the adjacent cabinet toe kicks.



1. Slide the step unit into the fully stored position.
2. Position toe kick extension in the precise cutout of the Step Unit.
3. Mark a vertical line on the toe kick extension, flush along where the backside of the toe kick would be. Use the adjacent cabinet as a guide. (Fig. 1)
4. Use this measurement to cut the toe kick extension to size.


**Fig. 1**



5. Attach the toe kick extension using a 5/8" flat head screw provided (Clamping toe kick extension to step unit can help alignment while attaching the screw).

6. Align the toe kick using the guidelines above, then glue the backside of the toe kick and tape or nail it to the toe kick extension.

**Warning:** Be aware of the step unit's front wheel location and other screw locations when nailing, especially if toe kick extension has been shortened.




## Adjusting the Depth of Step Unit:

## Warranty:


**Note:** The Step Unit has Adjustable Depth Positions to allow the back of the Step Unit to clear different cabinet handle/knob and appliance applications. Depending on appliance door design, the handle size and placement may impede the step unit. Measure before installing. Will not fit all applications.

Model Sizes Generally Designed For:	Handrail Length	Clearance Distance*				
		Position	1	2	3	4
21" US Bathroom and International Kitchens	A = 20 7/8" (530 mm)		1 1/2" (38mm)	2 1/2" (64mm)		
24" US Kitchen Cabinetry (Full-inset)	A = 23" (584 mm)		1 1/8" (29mm)	2 1/4" (57mm)	3 1/2" (89mm)	
24" US Kitchen (Frameless/Full Overlay)	A = 23 5/8" (600 mm)		1 1/8" (29mm)	2 1/8" (54mm)	3 1/8" (79mm)	4 1/8" (105mm)
27" Fridge Depth Cabinet (Max Clearance)	A = 26 7/8" (683 mm)		3 5/8" (92mm)	4 5/8" (117mm)	5 5/8" (142mm)	6 5/8" (168mm)



**Note:** Always choose the depth position so that when the Step Unit is deployed, the Top Step is the closest distance to the cabinet, cabinet pullknob/handle or appliance without interfering with them.

1. If adjustment to the depth of the Step Unit is needed, remove the Step Unit from the cabinet (See Installing/Removing Step Unit (Page 8)).
2. Determine the desired Depth Position (table above).
3. The Adjustable Stop is located on the top backside of the Step Unit's Handrail. Remove Adjustable Stop by unscrewing by hand (counter-clockwise).
4. Move Adjustable Stop to new location by screwing Adjustable Stop (clockwise) into Threaded Hole. Tighten firmly by hand.
5. Reinstall Step Unit (See Installing/Removing Step Unit). Adjust as necessary by repeating the steps above.



## WARRANTY - STEP 180 PLUS Integrated Cabinet Step Units

### Contact Information



Hideaway Solutions  
P.O. Box 923  
Little Compton, RI 02837

www.hideawaysolutions.com  
Phone 401-420-2042

### What The Warranty Covers

Our Limited Warranty Guarantees Our Products To Be Free From Defects In Material And Craftsmanship. Any Concerns With The Step 180 Should Be Addressed Immediately.

### Warranty Period

The Limited Warranty Coverage Is One Year From Date Of Purchase.

### What Hideaway Solutions Will Do To Correct Problems

In The Event Of Manufacturing Defects, Hideaway Solutions Will Repair Or Replace The Step Unit.

### What The Warranty Does Not Cover

We Do Not Cover


- Damage In Transit
- Failure To follow Installation Guide Correctly (Included With Step Unit)
- Wear And Tear On Original Wood Finish
- Inadequate Care, Abuse, Misuse Or Abnormal Use
- Accidents Due To Improper Use Of Product
- Damage Due To Environmental Or Natural Elements (Flood or Fire, etc.)
- Failure To Follow User Guide (Included With Step Unit)

# STEP 180 PLUS - SPECIFICATIONS


MODEL  
SIZES:

Height:	<input type="checkbox"/> 34 1/4" (870 mm)	Depth:	<input type="checkbox"/> 20 7/8" (530 mm)	<input type="checkbox"/> 23" (584 mm)
	<input type="checkbox"/> 32" (813 mm)		<input type="checkbox"/> 23 5/8" (600 mm)	<input type="checkbox"/> 26 3/4" (680 mm)


**SIDE VIEW** - Extended Closed Position




**FRONT VIEW** - Extended And Deployed Positions



**TOP VIEW** - Mounted Between Base Cabinet & 2nd Base Cabinet



**TOP VIEW** - Mounted Between Base Cabinet & End Panel



## STEP 180 PLUS

**Cabinet Size (Depth)**  
(Generally Designed For):

**Cabinet Space requirements:**

Width (between cabinets) \_\_\_\_\_

Height (Minimum) \_\_\_\_\_

Unit Depth \_\_\_\_\_

**Step Units Deployed Clearances:**

Max Clearance Depth (From Cabinet Frame) \_\_\_\_\_

Overall Width (From Center Of Unit) \_\_\_\_\_

Step Width (Usable) \_\_\_\_\_

Top Step Height \_\_\_\_\_

Top Step Depth \_\_\_\_\_

Max Extended Distance (From Cabinet) \_\_\_\_\_

Weight (Step Unit) \_\_\_\_\_

Weight Limit (Duty Rating) \_\_\_\_\_

Country of Origin \_\_\_\_\_

### 34 1/4" (870 mm) tall models

21" (US Bathroom & Intl Kitchens)	24" (US Kitchen "Full-inset")	24" (US Kitchen "Frameless/Full Overlay")	27" (Fridge Depth Cabinet "Max Clearance")
1 1/2" (38 mm)			
34 1/4" (870 mm)			
20 7/8" (530 mm)	23" (584 mm)	23 5/8" (600 mm)	26 7/8" (683 mm)
2 1/4" (57 mm)	3 1/2" (89 mm)	4 1/8" (105 mm)	6 5/8" (168 mm)
16" (406 mm)			
14 1/4" (362 mm)			
14 3/4" (375 mm)			
7" (178 mm)	8" (203 mm)	8" (203 mm)	8" (203 mm)
18 1/2" (470 mm)	20 7/8" (530 mm)	21 1/2" (546 mm)	24" (610 mm)
16 lbs (7.3 kg)	19 lbs (8.6 kg)	19 lbs (8.6 kg)	22 lbs (10 kg)
200 lbs (90.7 kg)			

### 32" (813 mm) tall models

21" (US Bathroom & Intl Kitchens)	24" (ADA Kitchen)
1 1/2" (38 mm)	
32" (813 mm)	
20 7/8" (530 mm)	23 5/8" (600 mm)
2 1/4" (57 mm)	4 1/8" (105 mm)
15" (381 mm)	
13 1/4" (337 mm)	
13 3/4" (349 mm)	
7" (178 mm)	8" (203 mm)
18 1/2" (470 mm)	21 1/2" (546 mm)
15 lbs (6.8 kg)	18 lbs (8.2 kg)
200 lbs (90.7 kg)	

Designed and Manufactured in the USA

Does Not Include Toe Kick, Face Panel, Pull Handle Or Cabinets

## Contact Information



Hideaway Solutions, LLC  
PO BOX 923  
Little Compton, RI 02837

www.hideawaysolutions.com  
Phone 401-420-2042

**WARRANTY** - The Limited Warranty Coverage Is One Year From Date Of Purchase. (see page 7 for details)